

2937 Model Group 1 Mechanical Safe Lock

**MEETS FEDERAL SPECIFICATION
FF-L-2937**



- Underwriters Laboratories Listed Group 1.
- Meets Federal Specification FF-L-2937.
- Stainless steel bolt withstands a minimum of 600 lbs. of side and end load.
- Dial spindle incorporates carbide barrier pins and a shear line to control the point of separation in a forced entry attempt.
- Three all metal wheels provide for 1,000,000 unique theoretical combinations.
- Resistance to expert manipulation tested and verified by Underwriters Laboratories to exceed 20 man-hours.
- Built to provide a high level of security for government and defense industry applications.
- Internal relock trigger secures the lock in the event of a burglar's punch attack.
- Integral thermal relock component protects against thermal attacks.
- Two-way drive cam and two-way dial spindle combine to allow mounting right-hand, left-hand, vertical-up, or vertical-down.
- Uses a standard S&G® three wheel change key (U8 or U9).

Locks, Dials & Rings

Order Number	No. of Wheels	Notes
2937-200	3	includes lock, dial* and ring, plus an extra, short, drilled and tapped lock bolt for some Mosler retrofit applications

2937 Individual Components

Order Number	Description
2937-002	Spy-Proof® dial* only
2937-003	dial ring and dust cover only
2937-004	dust cover only

* Dial spindle length will accommodate a maximum door thickness of 3.6 (91.4 mm)

