

SARGENT AND GREENLEAF®

A Subsidiary of Stanley Security Solutions, Inc.

6128 and 6129 ASERIES™ ATM Locks



- Underwriters Laboratories Listed Type 1, VdS Class 2, CEN B, A2P B/E, and RoHS compliant.
- Both models feature a motor-driven lock bolt which offers a high level of security by eliminating the threat of vibration and bouncing attacks.
- Up to thirty users—Both models offer one programmer code, two officer codes, four administrator codes, and ten user codes.
- Multiple User, Dual Control, and Manager/Employee modes selectable and changeable at any time by entering a special keypad command.
- 400-event, time and date stamped audit trail managed by easy-to-use PC-based software. To read audit trail information, you will need the optional audit trail software kit (part #6103-120). Time, date, and event duration information is generated and stored in the lock so that it is not susceptible to time drift.
- Snap-in touch key reader allows fast, accurate transfer of audit trail data.
- Both models incorporate a penalty time feature to prevent opening by entering sequential or random codes until a valid code is found.
- Both models offer time delay of one to ninety-nine minutes.
- Both models offer a duress capability, allowing a distress signal to be sent through the customer's central alarm system in the event of an emergency. An optional duress module (part #6102-090) is required to use this function.
- The 6128 ASERIES™ Lock is made for boltwork blocking applications that do not require direct attachment of the lock bolt to the safe's boltwork.
- The 6129 ASERIES™ Lock is designed for direct boltwork attachment and will push and pull 2.24 lbs. (10 newtons), with a maximum load of 5.6 lbs. (25 newtons).
- Some models are equipped with a bolt position indicator that closes a circuit when the lock bolt is in either the locked or unlocked position (see part number table below).

Lock Kits—lock, keypad, keypad extension, serial number plate

6128 ASERIES™ Order Number	6129 ASERIES™ Order Number	Non-Tamper Keypad	Keypad Extension	Bolt Position Indicator	Reset Code
6128-140	6129-140	yes	yes	no	no
6128-240	6129-240	yes	yes	yes	no



Audit software that runs on your Windows® 95, Windows® 98, Windows® Me, Windows® 2000, and Windows® XP operating system, cable with a Dallas® key receptor, and a Dallas® iButton® for transferring the audit information from the lock to your computer. Check your computer to see whether you will need the serial adapter or USB adapter. The appropriate driver software is included with each type of adapter. The keypad extension base and audit trail software kit are both needed to download, view, and manage time and date-stamped audit information captured by a 6128 or 6129 lock.

6103-120—Audit trail software on CD, serial adapter with cable, and Dallas® iButton®.

6103-102—USB adapter with cable only.

6104-006—Extra Dallas® iButton® (red fob).