

# SARGENT AND GREENLEAF®

A Subsidiary of Stanley Security Solutions, Inc.

## 6870 Series Key Operated Safe Lock



- Underwriters Laboratories Listed under Standard 437 as a Security Container Lock.
- Same mounting footprint as S&G® standard size combination locks, with the key hole in the same place as the spindle hole. Key hole through the safe door must be at least 1/2" (12,7 mm) in diameter.
- True double-bitted lock with nine opposing brass levers and a mechanism that permits changing to new keys in seconds, with no special tools.

### 6870 Locks with Keys

Order Number	Keys Included	Notes
6870-006	2	keys are for a maximum door thickness of 2.26" (57,4 mm)
6870-016	3	keys are for a maximum door thickness of 2.26" (57,4 mm)
6870-026	4	keys are for a maximum door thickness of 2.26" (57,4 mm)
6870-008	2	keys are for a maximum door thickness of 4.22" (107,1 mm)
6870-018	3	keys are for a maximum door thickness of 4.22" (107,1 mm)
6870-028	4	keys are for a maximum door thickness of 4.22" (107,1 mm)

### 6870 Pre-Cut Key Sets

Two Key Set	Three Key Set	Four Key Set	Notes
6870-112	6870-113	6870-114	pre-cut keys for 2.26" (57,4 mm) max door thickness
6870-132	6870-133	6870-134	pre-cut keys for 4.22" (107,1 mm) max door thickness
6870-202	6870-203	6870-204	pre-cut bit sets for use with 6870-200 stem

### Detachable Bits

Order Number	Notes
6870-200	key stem only for detachable bit for 7.57" (192,3 mm) maximum door thickness
6870-201	uncut detachable bit for use with key stem listed above

### Key Blanks

Order Number	Notes
6870-110	for 2.26" (57,4 mm) max door thickness
6870-130	for 4.22" (107,1 mm) max door thickness



**6870-370 Guide Tube**—Guides the key into the lock, and is suitable for thick doors and insulated doors. Tube length is 1 meter, and can easily be cut to length. Optional tube is not included with locks.