

Electronic Safe Lock Accessories



2004-600—Opens or closes a circuit when the lock bolt is retracted. Easily fit this BPI module to any Z⁰³ Rotarybolt® or any Z⁰² or Z⁰³ D-Drive lock.



2004-700—Add extra boltwork attachment points to any Z⁰³ Rotarybolt® or any Z⁰² or Z⁰³ D-Drive lock with “wings.” Ideal for lightweight safes without bolt control handles. Pushes and pulls 2.5 lbs. (11.12 Newtons). Part number 2004-700 is for a pair of wings.



6102-090—Opens an alarm circuit when the lock’s combination is entered one number up on the last code digit. Requires connection to an existing alarm system. Use with a properly configured 6124, 6125, 6126, 6127, Z⁰³ Rotarybolt®, Z⁰² D-Drive, or Z⁰³ D-Drive lock.

6102-100—The same duress feature as the 6102-090 and remote enable. A 5 to 12 Vdc input from any source will either enable or disable the lock, depending on how you set the selector switch. The enable/disable portion of the module works with any S&G® electronic safe lock, with the exception of the Model 6150. The duress feature works with any properly configured 6124, 6125, 6126, 6127, Z⁰³ Rotarybolt®, Z⁰² D-Drive, or Z⁰³ D-Drive lock.



6101-203—The keypad extension base incorporates a port that allows the downloading of audit information from the lock to a Dallas® iButton®. It mounts underneath the keypad. For use with 6126, 6127, 6128, and 6129 locks.



Audit software that runs on your Windows® 95, Windows® 98, Windows® Me, Windows® 2000, and Windows® XP computer, cable with a Dallas® key receptor, and a Dallas® iButton® for transferring the audit information from the lock to your computer. Check your computer to see whether you will need the serial adapter or USB adapter. The appropriate driver software is included with each type of adapter. The keypad extension base and audit trail software kit are both needed to download, view, and manage time and date-stamped audit information captured by a 6126 or 6127 lock.

6103-130—Audit software on CD, serial adapter with cable, and Dallas® iButton®.

6103-131—Audit software on CD, USB adapter with cable, and Dallas® iButton®.

6103-102—USB adapter with cable only.

6104-006—Extra Dallas® iButton® (red fob).



6350-001—6300 software kit with included data keys and serial interface reader/cable. Windows 95, Windows 98, Windows ME, Windows 2000 and Windows XP-based application for programming the 6300 multiple compartment safe lock and for reading, printing, and archiving audit trail information.
(Also order the 6103-102 USB adapter cable kit if your computer does not have a serial port.)



6215-001—Time delay indicator mirrors the time delay period of a 6120 or 6123 lock, and can be remotely located. Displays time delay and opening window. Built-in sounder echoes the time delay beeps emitted by the lock.

6120-060—Cables and junction box needed to hook up the 6215-001.



6130-100—The Spy-Proof® cover makes it difficult for anyone to see which buttons are pressed as a code is entered. It’s easily added to any standard two-battery keypad (not for use with one-battery keypads or the Biometric Keypad). It does not interfere with keypad removal for battery replacement. Keypad not included.



6120-050—20 cm (7.87) long cable extension.
6120-051—40 cm (15.75) long cable extension.
6120-057—60 cm (23.62) long cable extension.
All three kits include wire ties and heat-shrink to provide secure, trouble free connections.



6120-064—Control two locks with a single keypad, based on microswitch activation. Kit includes cable assembly, attached microswitch, heat-shrink, wire ties, and tie blocks.