

SARGENT AND GREENLEAF®

A Subsidiary of Stanley Security Solutions, Inc.

Mechanical Safe Lock Features Chart

	6730 Series	6731 Series	6741 Series	6738 Series	6748 Series	6630 Series	6631 Series	6651 Series	8410 Series	8430 Series	8550 Series	8560 Series
UL Listed Group 2	✓	✓	✓	✓	✓							
UL Listed Group 2M						✓	✓	✓				
UL Listed Group 1									✓		✓	
UL Listed Group 1R										✓		✓
VdS Class 1	✓		✓	✓				✓				
VdS Class 2		✓									✓	
CEN A	✓		✓	✓				✓				
CEN B		✓									✓	
CNPP A2P			A/E		A	B	B				B/E	
DNV 3492						✓	✓				✓	
China CCC	✓	✓										
Number of Wheels	3	4	3	4	4	3	4	3	3	3	3	3
Theoretical Combinations	1,000,000	100,000,000	1,000,000	1,000,000	1,000,000	1,000,000	100,000,000	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000
Typical Dialing Tolerance*	± 0.5	± 0.5	± 1.0	± 0.5	± 1.0	± 0.5	± 0.5	± 1.0	± 0.5	± 0.5	± 0.5	± 0.5
Duress Capability	ORDER 6738-003			ORDER 6738-013	ORDER 6748-013							
Time Delay	ORDER 6205-002											
Lever Position Indicator	ORDER 6738-005			ORDER 6738-013	ORDER 6748-013							

* Typical dialing tolerance is what you would expect to experience in an installed lock. Theoretical dialing tolerance is always slightly greater (usually about ± 0.4 numbers greater).

